




FEATURES

- Ceramic core wire wound construction with high Q and high SRF
- AEC-Q200 qualified
- Lead-free reflow soldering as referenced in JEDEC J-STD 020D and RoHS compliant
- Operating Temperature: -55~+125 °C (Including self-temperature)
- Quantity: 2000pcs

APPLICATION

- Resonant circuits, impedance matching for
- Antenna amplifiers
- Mul media
- Wireless communication systems
- Automotive electronics
- GPS (Global Positioning System)
- Low-pass filters for data lines

[illegible]

	(nH)		(Hz)		Q (MHz)	(mA)	(Ω)	(MHz)
WCIV2012HF-R10J								
WCIV2012HF-R11J								
WCIV2012HF-R12J								
WCIV2012HF-R15J								
WCIV2012HF-R18J								
WCIV2012HF-R22J								
WCIV2012HF-R24J								
WCIV2012HF-R27J								
WCIV2012HF-R33J								
WCIV2012HF-R39J								
WCIV2012HF-R47J								
WCIV2012HF-R56J								
WCIV2012HF-R62J								
WCIV2012HF-R68J								
WCIV2012HF-R75J								
WCIV2012HF-R82J								
WCIV2012HF-1R0J								

Inductance Tolerance: C=±0.2nH , S=±0.3nH, J=±0.5%

